

H8508 Impact Wrench and Drill – 7/16" Hex and 1/2" Square Drive



48330

CAT. NO.	UPC NO.	DESCRIPTION
CE 48330	48330	1/2" Impact Wrench, 7/16" hex quick-change chuck with 1/2" square adapter
CE 48329	48329	1/2" Impact Wrench, 1/2" square drive
54923	54923	HTMA Male Coupler
54925	54925	HTMA Female Coupler

- Super Spool™ for use on Open- and Closed-Center hydraulic systems.
- Reversible operation.
- High torque for drilling salt-cured and creosoted poles.
- Heat-insulated handle, ergonomically positioned for comfort.
- Twin hammer impact mechanism for high performance and reliability.
- Well-balanced for comfortable operation.

SPECIFICATIONS

Capacity	7/16" quick-change chuck or 1/2" square drive
System	Super Spool™ selector control
Weight	7.1 lbs. (3.2 kg)
Length	8.2" (208 mm)
Width	4.2" (107 mm)
Height	10.6" (269 mm)
Flow Range	4-10 gpm (15-38 lpm)
Optimum Flow Range	5 - 8 gpm (19 - 30 lpm)
Operating Pressure	1,000 - 2,500 psi (69 - 170 bar)
Torque	400 ft.-lb. at 8 gpm (542.3 Nm at 30 lpm)
Pressure Port Thd.	3/4 - 16 SAE O-Ring
Return Port Thd.	3/4 - 16 SAE O-Ring

H8508 Variable Torque Impact Wrench and Drill – 7/16" Hex and 1/2" Square Drive



48755

CAT. NO.	UPC NO.	DESCRIPTION
CE 48755	48755	1/2" Impact Wrench, 7/16" hex quick change chuck with 1/2" square adapter, variable torque control
CE 48760	48760	1/2" Impact Wrench, 1/2", square drive, variable torque control
54923	54923	HTMA Male Coupler
54925	54925	HTMA Female Coupler

- Super Spool™ for use on Open- and Closed-Center hydraulic systems.
- Internal control prevents overspeeding, allows flows up to 12 gpm (45 lpm).
- Reversible operation.
- High torque for drilling salt-cured and creosoted poles.
- Heat-insulated handle, ergonomically positioned for comfort.
- Twin hammer impact mechanism for high performance and reliability.
- Well-balanced for comfortable operation.
- Variable torque control can be adjusted from 80 to 400 ft.-lb. (108 to 542 Nm)

SPECIFICATIONS

Capacity	7/16" quick-change chuck or 1/2" square drive
System	Super Spool™ selector control
Weight	7.1 lbs. (3.2 kg)
Length	8.2" (208 mm)
Width	4.2" (107 mm)
Height	10.6" (269 mm)
Flow Range	4 - 12 gpm (15 - 45 lpm)
Optimum Flow Range	5 - 8 gpm (19 - 30 lpm)
Operating Pressure	1,000 - 2,500 psi (69 - 170 bar)
Torque	Adjustable from 80 - 400 ft.-lb. (108 - 542 Nm)
Pressure Port Thd.	3/4 - 16 SAE O-Ring
Return Port Thd.	3/4 - 16 SAE O-Ring