

## Breakers – 45 lb. (20.4 kg)

HPB45-1AVS



- Great for breaking sidewalks and curbs or driving ground rod, and for other small demolition jobs.
- Clean modular design with few protrusions to irritate operators' legs.
- High blow energy provides maximum breaking power.
- Integral rubber damper reduces chisel noise.
- Low noise and vibration levels.
- AVS tools have patented spring-dampened handles that reduce vibration transmitted to the operator by 80%-90%.
- Two-step trigger.

### SPECIFICATIONS

#### Weight

HPB45-1	53 lb (24.1 kg)
HPB45-2	46 lb (20.9 kg)
HPB45-1AVS	54 lb (24.5 kg)
HPB45-2AVS	47 lb (21.3 kg)

#### Vibration Level

HPB45-1 & HPB45-2	11.4 m/s <sup>2</sup>
HPB45-1AVS & HPB45-2AVS	5.3 m/s <sup>2</sup>

#### Sound Power Level

HPB45-1 & HPB45-1AVS	LWA=110 dB
HPB45-2 & HPB45-2AVS	LWA=109 dB

#### Blow Energy

63 ft-lb (85 Joules)
----------------------

#### Blow Frequency

2160/min
----------

#### Oil Flow

5-8 gpm (18-30 lpm)
---------------------

#### Length

HPB45-1 & HPB45-1AVS	28.5" (731 mm)
HPB45-2 & HPB45-2AVS	26.5" (682 mm)

#### Hydraulic System

Open-Center
-------------

#### Pressure & Return Ports

1/2" BSP
----------

#### Whip Hose Threads

1/2" NPTF
-----------

CAT. NO.	UPC NO.	DESCRIPTION
HPB45-1	02195	Breaker – 1-1/8 x 6" tool shank size, cushioned/dampened handles
HPB45-2	02196	Breaker – 1 x 4-1/4" tool shank size, cushioned/dampened handles
HPB45-1AVS	02197	Breaker – 1-1/8 x 6" tool shank size, cushioned/spring-dampened handles
HPB45-2AVS	02198	Breaker – 1 x 4-1/4" tool shank size, cushioned/spring-dampened handles

## Breakers – 55 lb. (25.2 kg)



HPB55-1

- High blow energy provides maximum breaking power that can handle big demolition tasks with ease.
- Clean modular design with few protrusions to irritate operators' legs.
- High blow energy provides maximum breaking power.
- Integral rubber damper reduces chisel noise.
- Low noise and vibration levels.
- AVS tools have patented spring-dampened handles that reduce vibration transmitted to the operator by 80%-90%.
- Two-step trigger.

### SPECIFICATIONS

#### Weight

HPB55-1 & HPB55-2	55 lb (25.2 kg)
HPB55-1AVS & HPB55-2AVS	56 lb (25.6 kg)

#### Vibration Level

HPB55-1 & HPB55-2	11.4 m/s <sup>2</sup>
HPB55-1AVS & HPB55-2AVS	9.0 m/s <sup>2</sup>

#### Sound Power Level

LWA=112 dB
------------

#### Blow Energy

81 ft-lb (110 Joules)
-----------------------

#### Blow Frequency

1860/min
----------

#### Oil Flow

5-8 gpm (18-30 lpm)
---------------------

#### Length

30" (760 mm)
--------------

#### Hydraulic System

Open-Center
-------------

#### Pressure & Return Ports

1/2" BSP
----------

#### Whip Hose Threads

1/2" NPTF
-----------

CAT. NO.	UPC NO.	DESCRIPTION
HPB55-1	02199	Breaker – 1-1/8 x 6" tool shank size, cushioned/dampened handles
HPB55-2	02200	Breaker – 1 x 4-1/4" tool shank size, cushioned/dampened handles
HPB55-1AVS	02201	Breaker – 1-1/8 x 6" tool shank size, cushioned/spring-dampened handles
HPB55-2AVS	02202	Breaker – 1 x 4-1/4" tool shank size, cushioned/spring-dampened handles