

## Polyurethane Low Pressure Hose\*, Orange, Non-Conductive



- Certified nonconductive orange polyurethane.
- Double rayon braid.
- Working pressure 2,250 psi (155 bar) tested to 75 kV/ft. for five minutes.

CAT. NO.	UPC NO.	QTY.	DESCRIPTION
108270	40249	2	2-3/8" x 5' (10 mm x 1.5 m) I.D. Hoses bonded together with 3/8" (10 mm) NPTF male fitting on one hose and 1/2" (13 mm) male NPTF fitting on the other hose
108271	40250	2	2-3/8" x 8' (10 mm x 2.4 m) I.D. Hoses bonded together with 3/8" (10 mm) NPTF male fitting on one hose and 1/2" (13 mm) male NPTF fitting on the other hose
108272	43036	2	2-3/8" x 10' (10 mm x 3 m) I.D. Hoses bonded together with 3/8" (10 mm) NPTF male fitting on one hose and 1/2" (13 mm) male NPTF fitting on the other hose
108273	40251	2	1-3/8" x 15' (10 mm x 4.6 m) I.D. Hose and 1-1/2" x 15' (13 mm x 4.6 m) hose bonded together with 3/8 in (10 mm) NPTF male fitting on one hose and 1/2" (13 mm) NPTF male fitting on the other hose
108274	40252	2	1-3/8" x 25' (10 mm x 7.6 m) I.D. Hose and 1-1/2" x 25' (13 mm x 7.6 m) hose bonded together with 3/8" (10 mm) NPTF male fitting on one hose and 1/2" (13 mm) NPTF male fitting on the other hose

## Low Pressure Hose\*



- Steel (conductive).
- Wire braid reinforced.
- SAE 100 RIAT Hose.
- Working pressure 2,000 psi (140 bar)

CAT. NO.	UPC NO.	QTY.	DESCRIPTION
40284	40284	2	1/2" x 25' (13 mm x 7.6 mm) wire braid hoses with 1/2" (13 mm) NPTF male fittings at both ends

NOTE: Steel braid hoses are not intended for use near energized lines or equipment!

\*Hose assemblies come without quick-disconnect couplers, which must be ordered separately .